

STURDY Backflow Prevention Valve



Flood damage can prove very expensive and prevention is far more cost-effective. This economically priced EN certified valve prevents backflow into residential and commercial premises via the drain systems, toilets or sewers.

The backflow valve can be installed in horizontal sewage pipes within the building or in manholes/access chambers outside the building.

The valves come in standard sizes to fit pipes at 110, 160 and 200mm.

The economically priced valves are EN certified and meet UK regulation BS EN13564-1:2002.

The faceplate's guard and gasket are designed to protect against damage by rodents and block their entry.

The valve has a smooth interior surface to prevent any sediment collection and to ensure smooth flow.

The valves feature a locking lever to manually close the valve in both directions. To service, the stainless steel screws are simply removed giving access to the flap and gasket.

Fits Pipe Diameter (mm)	Dimensions (LxWxH)	Weight (kg)
110*	287 x 188 x 210	0.88
160	318 x 202 x 228	1.89
200	480 x 311 x 328	3.6

*Sturdy Products supply the 110mm (4") version as standard but the other sizes can be supplied if required



STURDY PRODUCTS LIMITED
Blessington Industrial Estate, Blessington, Co Wicklow
Tel: +353 (0)45 865044 Fax: +353 (0)45 865721
E-mail: sales@sturdyproducts.com Website: www.sturdyproducts.com